

SCD 19100

1 MPixel 19" Color Display



- Fully automated luminance stability through the Integrated Stability System (ISS)
- CIE/DICOM compliant gray scale response built into the display
- Adjustable color point for optimized display matching
- Fully supported by the SMfit® Total Care family of quality assurance tools
- 5 user defined 10 bit look up tables adaptable to diverse reading and viewing environments
- Gamma response calibrated during manufacturing to provide consistent image quality from one display to the next
- Code protected key pad to ensure proper alignment
- Built-in connector for spotmeter
- Internal silent power supply

display SOLUTIONS

Eizo SCD Series of color displays meets the demanding requirements of Medical Imaging with the advantages of digital flat panel technology for reliable diagnosis.

The SCD 19100 produces color and gray scale images for the accurate, high-speed presentation of motion studies and dynamic images in Cardiac Imaging, Ultrasound and Nuclear Medicine.



SCD 19100

1 MPixel 19" Color Display

Technical specifications	
Display performance	
Resolution	1280 x 1024
Display area (W x H) in mm	376 x 301
Panel technology	Color, TFT, IPS, dual domain
Viewing angle	170° H and V
Contrast ratio	450:1
Luminance	280 cd/m ² (82 fL)
Calibrated luminance	DICOM, 125 cd/m ² (36 fL) DICOM, 160 cd/m ² (47 fL) CIE, 125 cd/m ² (36 fL)
LUT	10 bit
Number of gray shades	1024
Antireflection coating	Anti-glare
Signal inputs	
Connectivity	DVI-I 15pin-SubD
Supported signals	DVI, single link RGB (DVI-I, 15pin-SubD)
Supported formats	VGA, SVGA, XGA, SXGA non-interlaced, interlaced
Analog properties	
Line frequency	30 ... 100 kHz
Frame rate	50 ... 100 Hz
Impedance	75 Ω, 10 kΩ
Data interface	
Connectivity	RJ11, 6pin-MiniDIN, DVI
Supported signals	RS 232-Bus, DDC
Supported software	
SMfit® Total Care	Auto adjustment, stability, calibration and control tool (included in scope of delivery)
SMfit® Site Manager	Administrator tool
Backlight	
Technology	CCFL
ISS (Integrated Stability System)	Yes
Life time	50 000 h
Climatic conditions	
Operating temperature	0 ... +40 °C (32... +104 °F)
Within specifications	0 ... +35 °C (32 ... +95 °F)
Storage temperature	-20 ... +60 °C (-4 ... +140 °F)
Operating humidity	20% ... 80%, relative
Storage humidity	5% ... 95%, relative
Barometric pressure	1050 hPa ... 600 hPa

Technical specifications	
Power requirements	
Input voltage	100 ... 240 V AC, ± 10%
Power frequency	50 ... 60 Hz, ± 5%
Power consumption	< 60 W
Power save (analog)	DPMS
Power save (digital)	DVI-DMPM
Mechanical specifications	
Mechanical adaptation	VESA 100 mm x 100 mm
Degree of protection	IP20
Dimensions without stand (W x H x D) in mm	420 x 345 x 92
Weight without stand	6.6 kg
Weight with protective glass	7.2 kg
Design	
Mounting options	Ceiling suspension or desktop
Orientation	Landscape or portrait
Panel controls	
Controls	Key pad and OSD
Indicators	Power on/off
Approvals	
Safety	EN60601-1 CSA C22.2 No.601.1 UL60601-1
EMC	EN60601-1-2 limit B FCC Class A MPR II

Ordering data	
Model number	
Without stand: SCD 19100 C	6GF6210-2CA10
With protective glass, without stand: SCD 19100 CP	6GF6210-2CA20
Accessories	
Cable kit for full SMfit functionality	6GF6980-1TA08
Fixed stand	6GF6280-1DG
Multifunctional stand	6GF6988-8AA01 (without protective glass)
Multifunctional stand	6GF6988-8AA02 (with protective glass)
DVI transmission line (36 m)	6GF6010-0DA36

All product designations may be trademarks or product names of Eizo GmbH or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.


An obligation to provide the respective characteristics shall only exist, if expressly agreed in the terms of contract. Availability and technical specifications are subject to change without notice.

The information provided in this brochure contains descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products.



SCD 19102

1 MPixel 19" Color Display



- Fully automated luminance stability through the Integrated Stability System (ISS)
- CIE/DICOM compliant gray scale response built into the display
- Adjustable color point for optimized display matching
- Fully supported by the SMfit® Total Care family of quality assurance tools
- 5 user defined 10 bit look up tables adaptable to diverse reading and viewing environments
- Gamma response calibrated during manufacturing to provide consistent image quality from one display to the next
- State of the art video signal rendering; video standards: PAL, NTSC
- **Force Mode** for tailoring the display to even the most specialized timing requirements
- Code protected key pad to ensure proper alignment
- Built-in connector for spotmeter
- Internal silent power supply

display SOLUTIONS

Eizo SCD Series of color displays meets the demanding requirements of Medical Imaging with the advantages of digital flat panel technology for reliable diagnosis.

The SCD 19102 produces color and gray scale images for the accurate, high speed presentation of motion studies and dynamic images in endoscopy, surgery, cardiac imaging, and ultrasound.



SCD 19102

1 MPixel 19" Color Display

Technical specifications	
Display performance	
Resolution	1280 x 1024
Display area (W x H) in mm	376 x 301
Panel technology	Color, TFT, IPS, dual domain
Viewing angle	170° H and V
Contrast ratio	600:1
Luminance	280 cd/m ² (82 fL)
Calibrated luminance	DICOM, 125 cd/m ² (36 fL) CIE, 125 cd/m ² (36 fL) LINEAR, 160 cd/m ² (47 fL)
LUT	10 bit
Number of gray shades	1024
Antireflection coating	Anti-glare
Signal inputs	
Connectivity	DVI-I 15pin-SubD 4pin-Mini DIN BNC
Supported signals	DVI, single link RGB (DVI-I, 15pin-SubD) Y/C CVBS
Supported formats	VGA, SVGA, XGA, SXGA non-interlaced, interlaced
Force Mode	Yes
Analog properties	
Line frequency	30 ... 100 kHz
Frame rate	50 ... 100 Hz
Impedance	75 Ω
Data interface	
Connectivity	RJ11, 6pin-MiniDIN, DVI
Supported signals	RS 232-Bus, DDC
Supported software	
SMfit® Total Care	Auto adjustment, stability, calibration and control tool (included in scope of delivery)
SMfit® Site Manager	Administrator tool
Backlight	
Technology	CCFL
ISS (Integrated Stability System)	Yes
Life time	45 000 h
Climatic conditions	
Operating temperature	5 ... +40 °C (32... +104 °F)
Within specifications	5 ... +35 °C (32 ... +95 °F)
Storage temperature	-20 ... +60 °C (-4 ... +140 °F)
Operating humidity	20% ... 80%, relative
Storage humidity	5% ... 95%, relative
Barometric pressure	1050 hPa ... 650 hPa

Technical specifications	
Power requirements	
Input voltage	100 ... 240 V AC, ± 10%
Power frequency	50 ... 60 Hz, ± 5%
Power consumption	< 58 W
Power save (analog)	DPMS
Power save (digital)	DVI-DMPM
Mechanical specifications	
Mechanical adaptation	VESA 100 mm x 100 mm
Degree of protection	IP20
Dimensions without stand (W x H x D) in mm	422 x 348 x 95
Weight without stand	6.4 kg
Weight with protective glass	7.0 kg
Weight with stand	11.4 kg
Design	
Mounting options	Ceiling suspension or desktop
Orientation	Landscape or portrait
Panel controls	
Controls	Key pad and OSD
Indicators	Power on/off
Approvals	
Safety	EN60601-1 CSA C22.2 No.601.1 UL60601-1
EMC	EN60601-1-2 limit B FCC Class A MPR II

Ordering data	
Model number	
Without stand: SCD 19102 C	6GF6210-2EA10
With protective glass, without stand: SCD 19102 CP	6GF6210-2EA20
With multifunctional stand: SCD 19102 D	6GF6210-2EA01
Accessories	
Cable kit for full SMfit functionality	6GF6980-1TA08
Fixed stand	6GF6280-1DG
Multifunctional stand	6GF6988-8AA01 (SCD 19102 C)
Multifunctional stand	6GF6988-8AA02 (SCD 19102 CP)
DVI transmission line (36 m)	6GF6010-ODA36

All product designations may be trademarks or product names of Eizo GmbH or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.

An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Availability and technical specifications are subject to change without notice.

The information provided in this brochure contains descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products.

